

GOTECH "the best partner" to raise your competition

GT-6012 衝孔試驗機 Puncture Tester

GB 2679.7、ISO 3036、JIS-P 8134、TAPPI-T803

本機適用於紙板及瓦楞紙板衝孔強度試驗。在規定的試驗條件下，將試樣夾在衝孔試驗機上，用連在擺臂上的穿刺頭戳穿試驗，測定戳穿試樣時所消耗的能量。測試數據可以根據選擇的容量在刻度盤上讀出相應數值。

This machine is used for determining the puncture resistance of paperboards or corrugated boards. Under the specified test conditions, the specimen fixed in the puncture tester is pierced by the dart connected to the swing arm so as to determine the energy required for puncturing the specimen. The test data can be read directly from the scale according to the selected capacity.



	JIS-P8134	GB 2679.7、ISO 3036	TAPPI-T803
容量 Capacity (※請依規範選擇一種)	(A) Scale 0~53.5kg-cm	Scale 0~6J	(A) Scale 0~5.243J
	(B) Scale 0~107kg-cm	(+A) Scale 0~12J	(B) Scale 0~10.486J
	(C) Scale 0~214kg-cm	(+AB) Scale 0~24 J	(C) Scale 0~20.972J
	(D) Scale 0~428kg-cm	(+ABC) Scale 0~48J	(D) Scale 0~41.944J
	(E) Scale 0~26.75kg-cm	(E) Scale 0~3J	(E) Scale 0~2.622J
試樣 Specimen	175×175mm		
穿刺錐 Punch Head	高度1"，曲率半徑1.5mm Height 1", Radius 1.5mm		
擺錘形狀 Pendulum arm	90°圓弧臂 in the form of an arc of 90°		
正三角棱錐形高 Height of regular triangular	25±0.7mm		
兩板有效面積 Effective area of two plates	175×175 mm		
壓板夾持力 Clamping force	25~100kgf		
單位	kg-cm或焦耳(依規範配置)		
體積(約) Dimension(W×D×H)	85×40×76cm		
重量(約) Weight	140kg		

瞭解更多產品信息，請登錄我司網站 www.gotech.biz