

## GOTECH "the best partner" to raise your competition

### 硬度計 HARDNESS TESTER (made in Japan)

本硬度計系列廣泛適用於測量蜂巢狀、軟質或硬質橡膠以及塑料等材料之硬度。  
測定法：將本計垂直壓於被測物表面，指針所指之刻度，即為被測物之硬度。

These shore round style durometer are the most widely used instruments throughout the world for the hardness testing of cellular, soft and hard rubber, and plastic material.

Press on specimen face perpendicularly, the hardness of specimen will be indicated by pointer.



| 型式 Model                  | GS-701N   | GS-702N   | GS-706N                 | GS-709N                                    | ASKER-C   | ASKER-F                                   |
|---------------------------|---|---|-------------------------|--|---|---|
| 規範<br>Applicable Standard | JIS S 6050<br>JIS K 7312  | ASTM D 2240,<br>ISO-868, JIS-K7215                                      | JIS K 6301              | ASTM D 2240,<br>ISO-868, JIS-K7215         | SRIS-0101   | 高分子計器F型,<br>ASKER-F                       |
| 適用材料<br>Meas. Object      | Sponge, felt, soft rubber,<br>hard foam, bobbin<br>winding, potter's clay<br>海棉、毛氈、軟質橡膠、<br>硬質發泡膠、管紗、陶土 | hard plastic,<br>hard rubber,<br>soft plastic<br>硬質塑膠、<br>軟質橡膠、<br>軟質塑膠 | ordinary rubber<br>一般橡膠 | ordinary rubber, soft plastic<br>一般橡膠、軟質塑膠 | soft rubber, sponge,<br>plastic foam, textile winding<br>軟質橡膠、海棉、<br>發泡塑膠、紡織線 | foam rubber,<br>plastic foam<br>發泡橡膠、發泡塑膠 |
| 體積 Dimensions             | 60x110x27 mm  |   |                         |  | 58x76x30 mm   | 80x82x80 mm                               |
| 重量 Weight                 | 200g  |   |                         |  |   | 519g                                      |

| 型式 Model                  | ASKER-A                                | SHORE-XA  | SHORE-XD  | SHORE-XOOO  | GSD-719K  |
|---------------------------|--|---|---|---|---|
| 規範<br>Applicable Standard | ASTM-D2240A<br>JIS-K7215A<br>JIS-K6253 | ASTM-D2240  |   |   | JIS K 6253, JIS K 7215,<br>ISO7619, ISO 868,<br>ASTM D 2240 |
| 適用材料<br>Meas. Object      | general rubber<br>一般塑膠                 | rubber: soft vulcanized (i.e. tire)<br>elastomeric: GR-S, GR-1, neoprene,<br>flexible polyacrylic esters.<br>other: wax, felt, leather, ...etc.<br>橡膠、軟質硫化橡膠(如輪胎)、天然橡膠<br>合成橡膠: GR-S、GR-1, 合成橡膠、聚丙烯酸(脂)<br>其他: 臘、毛氈、皮革等 | hard rubber<br>plastic: rigid thermo-plastics,<br>plexiglas, vinyl sheet, ...etc.<br>硬質橡膠<br>塑膠、硬質塑膠(熱塑膠)<br>樹脂玻璃、乙稀薄片等 | plastic foam: soft foams,<br>open or closed cells<br>發泡塑膠(軟質發泡膠、<br>開放或封閉式蜂巢) | Ordinary rubber,<br>soft plastic<br>一般橡膠、<br>軟質塑膠           |
| 體積 Dimensions             | 58x76x30 mm                            |   |   |   | 59x134x39 mm  |
| 重量 Weight                 | 220 g (approx.)                        |   |   |   | 313 g   |

■ 尚供應LCD液晶數值式，軟硬橡膠用之各式硬度計。LCD digital type of the testers are also available.

瞭解更多產品資訊，請登錄我網網站 [www.gotech.biz](http://www.gotech.biz)