



高鐵儀器 精密卓越



GOTECH "the best partner" to raise your competition

VT-06 高粘度計(日本RION製造) Viscometer (made in Japan)

VT-06是用於大範圍黏度之量測，適合檢測如重油、油漆及黏著劑之類的工業用物質。其在食品與其他生產製造過程中，可用來做品質管制。於檢驗工程車輛及其他機械時，亦可用來量測液壓油、輕軸油與齒輪油等等。其原理是以固定速度之迴轉筒浸入要量測之液體中，當迴轉筒轉動時，黏度(扭力)所產生之阻力以一種特殊技術量測，進而可直接在螢幕顯示mPa·s或dPa·s之讀值。

The VT-06 viscometer is designed for quality control application in the manufacturing process of industrial products such as petrochemicals, paint and adhesives. With a wide viscosity measurement range, the VT-06 can also perform measurement for hydraulic and gear oil used in construction machinery. Measurement is performed by submerging a rotor in the fluid. The resistance to rotor movement caused by the viscosity (torque) is measured to obtain direct readings.



量測範圍 Measurement range	3號迴轉筒: 0.3 to 13 dPa.s (以3號杯量測) 1號迴轉筒: 3 to 150 dPa.s (以JIS 300 mL燒杯量測 * 1) 2號迴轉筒: 100 to 4000 dPa.s (以JIS 300 mL燒杯量測 * 1)	No.3 rotor: 0.3 to 13 dPa.s (with No.3 cup) No.1 rotor: 3 to 150 dPa.s (with JIS 300mL beaker * 1) No.2 rotor: 100 to 4000 dPa.s (with JIS 300 mL beaker * 1)
液體取樣之容量 Sample fluid capacity	1號與2號迴轉筒 (以JIS 300 mL燒杯量測 * 1) 約300 mL 3號迴轉筒 (以3號杯量測) 約170 mL 迴轉筒之末端與杯底間之距離約15 mm	No.1 and No.2 rotor (with JIS 300 mL beaker * 1) approx. 300mL No.3 rotor (with No.3 cup) approx. 170 mL Clearance between rotor end and cup bottom: About 15mm
量測準確度 Measurement accuracy	指示值的±10%以內 (再現性值±5%以內)	±10% of indicated value, reproducibility ±5%
迴轉筒旋轉速度 Rotor speed	62.5 rpm	
電源需求 Power supply	IEC LR6 (size AA) 鹼性電池或鎳氫充電電池或AC電源轉換器VA-05J IEC LR6 (size AA) alkaline batteries, nickel-hydride rechargeable batteries, AC adapter VA-05JA	
體積/重量 Dimensions and weight	175 (H) × 77 (W) × 40 (D) mm (不含突出部份 without protruding parts), 大約 approx. 260 g (不含電池 without batteries)	
標準配件 Standard accessories	1號迴轉筒 (直徑. 24 × 53 × 166 mm) SUS304*1 2號迴轉筒 (直徑. 15 × 1 × 113 mm) SUS304*1 3號迴轉筒 (直徑. 45 × 47 × 160 mm) SUS304*1 3號杯 (直徑. 52.6 × 75 mm) SUS304*1 延長桿 (900 mm · 300 × 3) SUS304*1 IEC LR6 (size AA) 鹼性電池 * 4	No.1 rotor (dia. 24 × 53 × 166 mm) SUS304*1 No.2 rotor (dia. 15 × 1 × 113 mm) SUS304*1 No.3 rotor (dia. 45 × 47 × 160 mm) SUS304*1 No.3 cup (dia. 52.6 × 75 mm) SUS304*1 Extension rod (900 mm · 300 × 3) SUS304*1 IEC LR6 (size AA) alkaline batteries * 4

瞭解更多產品信息，請登錄我司網站 www.gotech.biz



創於1977年
高鐵路科技股份有限公司
GOTECH TESTING MACHINES INC.

本廠: 台中市工業區24路28號
二廠: 台中市工業區24路31號
TEL: (04)23590061 FAX: (04)23591553
網址: www.gotech.biz E-mail: gt112@gotech.biz

高鐵路檢測儀器(東莞)有限公司
GOTECH TESTING MACHINES CO., LTD.

地址: 中國廣東省東莞市南城街道宏三路2號
TEL: 0769-89986666 22400899 FAX: 0769-22400699
E-mail: gt-d130@gotech.biz 手機: 13926831580

高特威爾檢測儀器(青島)有限公司
GOODTECHWILL TESTING MACHINES CO., LTD.

地址: 中國山東省青島市城陽區招商網毅合心園19號樓101
TEL: 0532-85931956 85931957 FAX: 0532-85931950
E-mail: gt-q101@gotech.biz 手機: 13708970121