

GOTECH "the best partner" to raise your competition

GT-7037-HH 安全鞋沖擊試驗機 Safety Shoes Impact Tester

ISO 20344-2021 5.4 5.16 · ISO 22568-1-2019 5.3 · ISO 22568-2-2019 5.3 ·
JIS T8101-2006 9.1 9.8 · GB/T 20991-2007 5.4 5.16 5.17

適用於安全鞋，防護鞋和職業鞋，也適用於其他用於個體防護的鞋類安全性能試驗方法，腳趾保護抗衝擊性能試驗及其趾骨保護裝置抗衝擊性能試驗。面板控制升級，採用PLC+HMI面板控制部份帶集成測速器的功能。

The GT-7037-HH and GT-7037-HHE are Gotech's new models of safety footwear impact tester for determining the resistance of safety shoes to impact with free fall drop test method. The control panel is upgraded to HMI touchscreen with speed recording feature.



面板控制	HMI
衝擊器重量 Mass of striker	5kg、20.0kg、22.7kg
衝擊能量範圍 Impact energy range	最大220J (衝擊器重量≥20kg時)
衝擊行程範圍 Impact stroke range	100mm ~ 1200mm
體積(約) Dimension (W×D×H)	90 cm × 76cm × 225 cm
重量(約) Weight (approx.)	240kg ※備註：客戶處需自備儀器安裝地基，確保儀器穩定性 Note: Requiring foundation to ensure the stability of tester.
電源 Power	1φ AC 220V 50Hz (依國別或指定 or specify)

瞭解更多產品資訊，請登錄我司網站 www.gotech.biz