

GOTECH "the best partner" to raise your competition

GT-7012-SA 萬能磨耗試驗機 Universal Wear Tester

JIS L1096-1999(A法) · CNS 12915-1991 · ASTM D3886-99(2015) · AATCC 119-2004 · AATCC 120-2004

適用於測試紡織品、針織物、地毯、長襪、毛氈、紗線、絲線、網狀物、塑膠片、橡膠片、皮革、紙張以及許多其他類似材料。使試樣與砂紙剛好接觸，進行表面磨耗測試，以評估試樣耐磨性。

The GT-7012-SA is specifically designed to assess the abrasion durability of materials including textiles, carpets, felt, threads, plastic sheets, rubber sheets, leather, and paper. The abrasion resistance of the sample can be determined by reciprocally rubbing it against sandpaper on the universal wear tester.



工作臺行程 Stroke length of reciprocating table	大約approx. 1"(25.4 mm)
扣環 Circular opening of clamping ring	φ94.0±1.3mm
鎖緊環 Tightening collar	φ95.3mm或以上 or more
鎖緊環至試樣距離 Upper edge of the tightening collar to specimen	<9.5mm
橡膠膜 Diaphragm	1.40±0.25mm
速度 Speed	100次/分鐘 ~ 130次/分鐘 (根據所選標準指定) 100cpm to 130 cpm (please specify)
壓力範圍 Pressure range	1 ~ 9 psi
表面試驗氣壓 Test pressure	0.28 kgf/cm ²
橡膠膜最大耐壓 Maximum pressure of diaphragm	7 kgf/cm ²
砝碼 Weight	2.0lb, 1.5 lb, 1.0 lb, 0.5 lb
計數器 Counter	0 ~ 999,999
計時器 Timer	0 ~ 999,999
體積 Dimensions (W×D×H)	35×74×48 cm
電源 Power	1φ AC 220V 6A (依國別或指定 or specify)

瞭解更多產品資訊，請登錄我司網站 www.gotech.biz