

GOTECH "the best partner" to raise your competition

GT-7042-RDHA 橡膠高溫回彈試驗機 High Temperature Elasticity Tester

GB/T 1681、ISO 4662

適用於測試彈性和發泡材料之耐衝擊能力。使用一定能量之衝擊錘衝擊試樣，觀察試樣在遭受撞擊震蕩時的彈性。

The GT-7042-RDHA is specifically designed to assess the rebound resilience of elastomers. This instrument applies the pendulum method, utilizing a hammer of specific mass to strike samples for assessing rebound resilience.



衝擊能量 Impact energy	0.5J
反彈系數顯示範圍 Resilience scale range	0~100 %
擺錘長度 Length of pendulum	204 mm
落下角度 Drop angle	90°
夾持方式 Grip	氣動夾持 Pneumatic grip
試樣厚度可調整範圍 Specimen thickness range	0 ~ 25 mm
移動軸最小標示刻度 Minimum graduation on the scale	1 mm
預熱溫度 Preheat temp. range	常溫+10~100°C Ambient temperature+10°C~100°C
連續打擊 Repeated impact	自動回擺機構 Auto-return mechanism
體積 Dimensions	62 cm ×30 cm ×46 cm
重量(約) Weight (approx.)	90 kg

瞭解更多產品信息，請登錄我司網站 www.gotech.biz